

Bitzer 4V-10.2

Specifications

Brand	Bitzer
Туре	4V-10.2
Refrigerant	Freon
kW at 0°C/+40°C	26,8
kW at -5ºC/+40ºC	22,2
kW at -10°C/+40°C	18,2
kW at -20°C/+40°C	11,8
kW at -30°C/+40°C	7,1
kW at -40°C/+40°C	3,7
Unloaded Start	✓
On steel base frame	✓
Pressure safety switches	✓
Hp/Lp/Op	
Liquid receiver	✓
Oil separator	✓
Sight Glass	✓
Solenoid Valve	✓
Control panel	✓
m3 / h	33,07
Weight in kg.	142 kg
Sizes	1000x610x1040 mm
	(LxWxH)
Stock	1



Description

Used Bitzer 4V-10.2

Used Bitzer 4V-10.2 semi-hermetic reciprocating compressor on steel base frame. Complete with a pressure and safety switch, liquid receiver, oil separator, sight glass and control panel. The compressor has a displacement of 33,07 m³/h at 1450 RPM and 39,91 m³/h at 1750 RPM. *Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. *Optional we can also perform a new paint job and arrange the logistics.



















Your partner for used commercial and industrial refrigeration equipment



