

## Bitzer 6G.2

### Specifications

|                       |                            |
|-----------------------|----------------------------|
| Brand                 | Bitzer                     |
| Type                  | 6G.2                       |
| Refrigerant           | Freon                      |
| kW at 0°C/+40°C       | 102,3                      |
| kW at -5°C/+40°C      | 82,9                       |
| kW at -10°C/+40°C     | 66,4                       |
| kW at -20°C/+40°C     | 40,9                       |
| kW at -30°C/+40°C     | 23,4                       |
| Unloaded Start        | ✓                          |
| Oil level system AC&R | ✓                          |
| Sight Glass           | ✓                          |
| Solenoid Valve        | ✓                          |
| m <sup>3</sup> / h    | 153                        |
| Remarks               | Y.o.b. 1996                |
| Sizes                 | 1480x570x560 mm<br>(LxWxH) |
| Stock                 | 1                          |



### Description

#### Used Bitzer 6G.2

Used Bitzer 6G.2 open-type reciprocating compressor on Freon. Complete with Dutchi NI 6010011 electromotor 50 Hz-30 kW-1475 RPM, oil level system AC&R and a sight glass. The compressor has a displacement of 153 m<sup>3</sup>/h.

\*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we solely deliver our orders after performing an extensive test and an industrial cleaning. If requested we are happy to arrange your logistics.



