

Bitzer 6H-25.2Y-40P (x2) & 4CC-6.2Y-40P (x1)

Specifications

Brand	Bitzer
Type	6H-25.2Y-40P (x2) & 4CC-6.2Y-40P (x1)
Refrigerant	Freon
kW at -5°C/+40°C	170,5
kW at -10°C/+40°C	140,6
kW at -20°C/+40°C	92,2
kW at -30°C/+40°C	56,4
kW at -40°C/+40°C	30,6
On steel base frame	✓
Pressure safety switches	✓
Hp/Lp/Op	
Pressure gauges	✓
Hp/Lp/Op	
Condensing pressure switches	✓
Liquid receiver	✓
Liquid receiver ltr.	160
Oil separator	✓
Oil level system AC&R	✓
Liquid line filter drier	✓
Sight Glass	✓
Solenoid Valve	✓
m ³ / h	50 Hz - 253,5 m ³ /h / 60 Hz - 305,8 m ³ /h



Remarks	Y.o.b. 2005
Package / Rack	✓
Sizes	3450x900x2110 mm (LxWxH)
Stock	1

Description

Used Bitzer 6H-25.2Y-40P (x2) & 4CC-6.2Y-40P (x1)

Used Bitzer 6H-25.2Y-40P (x2) & 4CC-6.2Y-40P (x1) semi-hermetic reciprocating compressor on Freon. Complete with a Bitzer F1602N liquid receiver with a volume of 160 liters, oil separator, oil reservoir, liquid line filter drier, braced heat exchanger, DAB KVCX 15/80M water pump, and pressure and safety switches/gauges. *Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty, and industrial cleaning. *Optional we can also perform a new paint job and arrange the logistics.







