

Bitzer 4HTC-15K-40P (x2)

Specifications

Brand	Bitzer
Туре	4HTC-15K-40P (x2)
Refrigerant	CO2
Refrigerant type	R744
kW at 0ºC/+40ºC	59,2
kW at -5ºC/+40ºC	49,2
kW at -10ºC/+40ºC	40,3
On steel base frame	✓
Pressure safety switches	✓
Hp/Lp/Op	
Pressure gauges	✓
Hp/Lp/Op	
Condensing pressure	✓
switches	
Liquid receiver	✓
Liquid receiver ltr.	110
Oil separator	✓
Oil level system AC&R	✓
Liquid line filter drier	✓
Sight Glass	✓
Control panel	✓
m3 / h	50 Hz - 24 m³/h / 60 Hz -
	29 m³/h
Remarks	Y.o.b. 2017
Package / Rack	✓
Sizes	2160x1000x2100 mm
	(LxWxH)





Stock

1

Description

Used Bitzer 4HTC-15K-40P (x2)

Used Bitzer 4HTC-15K-40P (x2) semihermetic reciprocating compressor rack on CO2 (R744). Complete with an OCS COLD RLV 110L 0DS28 liquid receiver with a volume of 110 liters, oil separator, oil reservoir, Danfoss FC-103P15KT4P55 frequency converter, pressure, and safety switches/gauges, liquid line filter drier, and a control cabinet. The compressors have a total displacement of 24 m³/h at 50 Hz and 29 m³/h at 60 Hz. *Why choose for HOSBV? We are not

only the largest used refrigeration specialist in Europe, but also, we deliver all equipment solely if it has passed our extensive test. Warranty and industrial cleaning are included in your purchase. *If requested we are happy to arrange your shipment.

















N.P.	Bitze				C-15K-4 0 2813744	P
	de in Ge	rmany				I
Nennspannung	Frequ.	Betr.strom	Anlaufstrom	1	Fördervol.	Drehzahl
V 3Ph~ 380-420	Hz 50	A (max.) 27.1	A(Y) 81.0	A(YY) 132	m³/h 12.0	min ⁻¹ 1450
440-480	60	27.1	81.0	132	14.5	1750
P 65 ND/HD n	5 A.C	00 / 160 bár	-	142	and the	(
1702205						

















		tomatik P/S				
Metalgangen 2-4A +45 46 134 134	, 2090 Ka	Dato.: 06-10-2017				
Vor ref.:	2242/Aldi Nyk.Mors					
TavleID:		2017180				
Norm:		EN60 204-1				
Max Forsikring:	160A					
Nødvendig forsikring:	80A					
Netspænding:	400/23	400/230VAC				
Styrespænding:	230Vac	230Vac/24Vdc/10Vdc				
Systemjording:	TN-S					
IK Max:	6kA					
Frekvens:	50Hz	Kapslingsklasse: IP23D				





