

Bitzer 6G.2

Specifications

Brand	Bitzer
Type	6G.2
Refrigerant	Freon
kW at 0°C/+40°C	106,3
kW at -5°C/+40°C	88,0
kW at -10°C/+40°C	72,2
kW at -20°C/+40°C	46,8
kW at -30°C/+40°C	28,3
kW at -40°C/+40°C	15,2
Unloaded Start	✓
Capacity Control	✓
On steel base frame	✓
Pressure safety switches	✓
Hp/Lp/Op	
Liquid receiver	✓
Liquid receiver ltr.	25 l
Sight Glass	✓
m ³ / h	78,7 m ³ /h -153,0 m ³ /h
Sizes	1950x800x1270 mm (LxWxH)
Stock	1



Description

Used Bitzer 6G.2

Used Bitzer 6G-2 open-type reciprocating compressor on Freon. Complete with a elektromotor, Stahlbau Hopfgarten liquid receiver a volume of 25 l, pressure and safety switches, sight glass, and a control box. The compressors have a displacement of 78,7-153 m³/h at 900-1750 RPM. *Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty, and industrial cleaning. *Optional we can also perform a new paint job and arrange the logistics.





