

Your partner for used commercial and industrial refrigeration equipment

Bitzer 4EC-4.2Y

Specifications

Brand	Bitzer
Туре	4EC-4.2Y
Refrigerant	Freon
kW at -5ºC/+40ºC	14,4
kW at -10ºC/+40ºC	11,9
kW at -20ºC/+40ºC	7,7
kW at -30ºC/+40ºC	4,7
kW at -40ºC/+40ºC	2,4
kW at -45ºC/+40ºC	1,6
Sight Glass	1
m3 / h	50 Hz - 22,7 m³/h / 60 Hz
	- 27,4 m³/h
Remarks	Y.o.b. 2002
Remarks	We only offer the
	compressor overhauled,
	but we can offer a fast
	delivery time.
Weight in kg.	84 kg
Sizes	400x310x320 mm
	(LxWxH)
Stock	1

C. MA		< B34	Jer >	>		Typ 4	EC-4.		-
	BITZER K	ÜHLMAS Made i	HINEN n E.C.	IBAU G	MBH		662	700304	
	Nennspan V ∆ 3Ph~	Nung		Max.Be A (∆)	A (Y)		A (Y)	Fördervol m ³ /h	Drehzah min ⁻¹
	180-200	300-330	50	21,5	12,4	117,6	67,9	22,7	1450
	200-230	360-400	60	21,5	12,4	117,6	67,9	27,4	1750
	IP 65 NI 378 028-03	6 2 2	The second second	28 bar	ilae.	1			CE
	-	1 and	A COMPANY	by treas	LA PART	2	SED.	ALL ST	

Description

Used Bitzer 4EC-4.2Y

Overhauled Bitzer 4EC-4.2Y semihermetic reciprocating compressor on Freon with a sight glass. The compressor has a displacement of 22,7 at 50 Hz & 27,4 m³/h at 60 Hz. We only offer the compressor overhauled and we can offer a fast delivery time. Please contact us for more information! *Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. *If requested we are happy to arrange your logistics.



	- Bit	er	>		Typ 4 S.Nr. 6	EC-4. 62700		
BITZER K	ÜHLMASO Made i		IBAU G	MBH		662	700304	
Nennspar V ∆ 3Ph~	Nung VY3Ph~		Max.Be A (∆)	tr.strom		strom A (Y)	Fördervol. m ³ /h	Drehza min ⁻¹
180-200	300-330	50	21,5	12,4	117,6	67,9	22,7	1450
				12,4	117.6	67.9	27.4	1750