

Your partner for used commercial and industrial refrigeration equipment

Bitzer 6J-33.2Y

Specifications

| Brand | Bitzer |
|----------------------------|--|
| Туре | 6J-33.2Y |
| Refrigerant | Freon |
| kW at 0ºC/+40ºC | 77,7 |
| kW at -5ºC/+40ºC | 64,3 |
| kW at -10ºC/+40ºC | 52,7 |
| kW at -20ºC/+40ºC | 33,9 |
| kW at -30ºC/+40ºC | 20,0 |
| kW at -40ºC/+40ºC | 10,1 |
| Sight Glass | 1 |
| m3 / h | 50 Hz - 95,3 m³/h / 60 Hz |
| | $11E m^{3}/b$ |
| | - 115 m³/h |
| Remarks | We only offer the |
| Remarks | |
| Remarks | We only offer the |
| Remarks | We only offer the compressor overhauled |
| Remarks Weight in kg. | We only offer the compressor overhauled and we can offer a fast |
| | We only offer the compressor overhauled and we can offer a fast delivery time |
| Weight in kg. | We only offer the compressor overhauled and we can offer a fast delivery time 231 kg |
| Weight in kg. | We only offer the compressor overhauled and we can offer a fast delivery time 231 kg 850x450x450 mm |



Description

Used Bitzer 6J-33.2Y

Overhauled Bitzer 4J-33.2Y semihermetic reciprocating compressor on Freon with a sight glass. The compressor has a displacement of 95,3 m³/h at 50 Hz & 115 m³/h at 60 Hz. We only offer the compressor overhauled and we can offer a fast delivery time. Please contact us for more information! *Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. *If requested we are happy to arrange your logistics.



Your partner for used commercial and industrial refrigeration equipment



| -Bitzen | | | | Typ 6J-33.2 Y S.Nr. 663001796 | | | |
|------------------------|------------------|-----------|---------------------|----------------------------------|---------------------------------|-------------------------------|--|
| BITZER KÜHLI | ASCH ade in E | | | | 3001796 | | |
| Nennspannung V 3Ph~ | Frequ. Hz | | Anlaufstro A (Y) | A (YY) | Fördervol. m ³ /h | Drehzahl min ⁻¹ | |
| 380-420 | 50 | 60 | 147 | 262 | 95,3 | 1450 | |
| 440-480 | 60 | 60 | 147 | 262 | 115 | 1750 | |
| IP 54 ND/HD | max.1 | 9 /28 bai | 3 | | | (| |



