

Bitzer 6G.2

Specifications

Type 6G.2 Refrigerant Freon kW at 0°C/+40°C 106,3 kW at -5°C/+40°C 88,0 kW at -10°C/+40°C 72,2 kW at -20°C/+40°C 46,8 kW at -30°C/+40°C 28,3 kW at -40°C/+40°C 15,2 On steel base frame Pressure safety switches Hp/Lp/Op Sight Glass Solenoid Valve
kW at 0°C/+40°C 106,3 kW at -5°C/+40°C 88,0 kW at -10°C/+40°C 72,2 kW at -20°C/+40°C 46,8 kW at -30°C/+40°C 28,3 kW at -40°C/+40°C 15,2 On steel base frame ✓ Pressure safety switches ✓ Hp/Lp/Op Sight Glass ✓
kW at -5°C/+40°C 88,0 kW at -10°C/+40°C 72,2 kW at -20°C/+40°C 46,8 kW at -30°C/+40°C 28,3 kW at -40°C/+40°C 15,2 On steel base frame ✓ Pressure safety switches ✓ Hp/Lp/Op Sight Glass ✓
kW at -10°C/+40°C 72,2 kW at -20°C/+40°C 46,8 kW at -30°C/+40°C 28,3 kW at -40°C/+40°C 15,2 On steel base frame ✓ Pressure safety switches ✓ Hp/Lp/Op Sight Glass ✓
kW at -20°C/+40°C 46,8 kW at -30°C/+40°C 28,3 kW at -40°C/+40°C 15,2 On steel base frame Pressure safety switches Hp/Lp/Op Sight Glass
kW at -30°C/+40°C 28,3 kW at -40°C/+40°C 15,2 On steel base frame Pressure safety switches Hp/Lp/Op Sight Glass
kW at -40°C/+40°C 15,2 On steel base frame Pressure safety switches Hp/Lp/Op Sight Glass
On steel base frame Pressure safety switches Hp/Lp/Op Sight Glass
Pressure safety switches Hp/Lp/Op Sight Glass
Hp/Lp/Op Sight Glass ✓
Sight Glass ✓
Solenoid Valve
m3 / h 50 Hz - 126,8 m³/h / 60
Hz - 153,0 m³/h
Weight in kg. 153 kg
Sizes 2500x1500x1320 mm
(LxWxH)
Stock 1



Description

Used Bitzer 6G.2

Used Bitzer 6G.2 open-type reciprocating compressor on Freon with a sight glass. Complete with a Rotor XC200LK04 electric motor - 50 Hz - 30 kW - 1470 RPM. The compressor has a displacement between 78,7 m³/h and 153,0 m³/h.

*Why choose for HOS BV? We are not only the largest used refrigeration specialist in Europe, but we also deliver all equipment including an extensive test, warranty and industrial cleaning. *Optionally we can also perform a new paint job and arrange the logistics.



















Your partner for used commercial and industrial refrigeration equipment





