

Bitzer 6F.2

Specifications

Brand	Bitzer
Туре	6F.2
Refrigerant	Freon
kW at 0ºC/+40ºC	127,4
kW at -5ºC/+40ºC	105,7
kW at -10ºC/+40ºC	87,0
kW at -20ºC/+40ºC	56,7
kW at -30ºC/+40ºC	34,4
Unloaded Start	✓
Pressure safety switches	✓
Hp/Lp/Op	
Oil level system AC&R	✓
Sight Glass	✓
Solenoid Valve	✓
m3 / h	94,1 m³/h at 900 RPM &
	183 m³/h at 1750 RPM
Sizes	1480x770x700 mm
	(LxWxH)
Stock	1



Description

Used Bitzer 6F.2

Used Bitzer 6F.2 open-type reciprocating compressor on Freon. Complete with a electric motor - 50 Hz -30 kW - 1477 RPM, AC&R oil level system, pressure and safety switches. The compressor has a displacement of 94,1 m³/h at 900 RPM & 183 m³/h at 1750 RPM.

*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment solely if it has passed our extensive test. Warranty and industrial cleaning are included in your purchase. *If requested we are happy to arrange your shipment.















HOS BV

www.hosbv.com





	VisserNederland			nd	IEC 60034-1			
			SERVICI		E	3		
		and the second se	uty: S1			E/NDE:	6312C3	
			00L-4	PTC				
Ins.c	L.F		P: 55	Fix-	Α	IM: B3	/B5	
V		Hz	kW	rpm	Α	n%	Cos	
400	Δ	50	30.0	1477		93.8	0.89	
690	Y	50	30.0	1477	30.0	93.8	0.89	
443	Δ	60	33.0	1775	52.0	93.6	0.89	
752	Y	60	33.0	1775	30.0	93.6	0.89	
D. AD:	B48	906	1)2-19		KG	: 350	







