

Telemecanique ATS46D38N

Specifications

Brand	Telemecanique
Type	ATS46D38N
Product type	Soft starter
Capacity kW	22 kW
Stock	1



Description

Used Telemecanique ATS46D38N

Used Telemecanique ATS46D38N drive with the following specifications:

230V - 9 kW - 38A
400V - 18,5 kW
500V - 22 kW - 34A

Dimensions: 300x170x150 mm
(LxWxH).



Telemecanique			
ATS46D38N			
Power / Puissance			
VOLTS	208	230	480
HP (USA)	10	—	25
VOLTS	230	400	500
KW	9	18.5	22
IcL (A)	38	In (A)	34
MAX FUSE		See manual	Voir guide d'exploitation
SHORT CIRCUIT WITHSTAND		5KA	
WIRING		8 AWG/75° C	10 MM
TIGHTENING TORQUE		15 LB.IN	1.7 NM
		FUSIBLE MAX	TENUE AU COURT - CIRCUIT
		CABLAGE	
		SERRAGE	

Telemecanique	
Control / Contrôle	Power / Puissance
220...240V 1 phase 380...415V 50/60Hz 440...500V 2A max Consumption / Consommation 20VA	FREQUENCY : input 50/60HZ output 50/60HZ
input currents / Courants d'entree (02)arret / stop 20mA/24V --- (03)marche / run	UL CE SP
Auxiliary contacts (15..54) Contacts auxiliaires	LISTED 4507 IND CONT EQ
400V max Ith= 5A	EC 947-4-2 34 A ACB3A 323 50 10
IEC 337 AC11 : 240V 0.5A DC11 : 48V 0.5A B300	9802

