

Bitzer 6G-40.2Y (x2) / 66G-80.2Y

Specifications

Brand	Bitzer
Type	6G-40.2Y (x2) / 66G-80.2Y
Refrigerant	Freon
kW at 0°C/+40°C	205,0
kW at -5°C/+40°C	170,7
kW at -10°C/+40°C	140,6
kW at -20°C/+40°C	92,0
kW at -30°C/+40°C	55,9
kW at -40°C/+40°C	29,9
Unloaded Start	✓
Capacity Control	✓
On steel base frame	✓
Liquid receiver	✓
Liquid receiver ltr.	105
Oil separator	✓
Liquid line filter drier	✓
Sight Glass	✓
Solenoid Valve	✓
m ³ / h	50 Hz - 253,6 m ³ /h / 60 Hz - 305,8 m ³ /h
Package / Rack	✓
Sizes	2110x810x1400 mm (LxWxH)
Stock	3



Description

Used Bitzer 6G-40.2Y (x2) / 66G-80.2Y

Used Bitzer 6G-40.2Y (x2) & 66G-80.2Y semi-hermetic reciprocating compressor on Freon. Complete with a Bitzer F1052T liquid receiver, ESK Schultze OS 67FH oil separator and a liquid line filter drier. The compressor has a displacement of 253,6 m³/h at 50 Hz & 305,8 m³/h at 60 Hz.

*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment solely if it has passed our extensive test. Warranty and industrial cleaning are included in your purchase. *If requested we are happy to arrange your shipment.





