

# Sabroe SAB 128 HF

## Specifications

Brand	Sabroe
Type	SAB 128 HF
Refrigerant	NH 3 (ammonia)
kW at +10°C/+40°C	610,3*
kW at 0°C/+40°C	423,2*
kW at -5°C/+40°C	347,9*
kW at -10°C/+40°C	283,2*
kW at -20°C/+40°C	214,8*
kW at -30°C/+40°C	134,7*
kW at -40°C/+40°C	77,8
Capacity Control	✓
On steel base frame	✓
Oil separator	✓
Sight Glass	✓
Solenoid Valve	✓
Control panel	✓
m <sup>3</sup> / h	454,0 m <sup>3</sup> /h - 2950 RPM / 546,0 m <sup>3</sup> /h - 3550 RPM
Remarks	Y.o.b. 1997
Remarks	*Bigger electric motor needed
Sizes	2550x1000x1630 mm (LxWxH)
Stock	1



## Description

### Used Sabroe SAB 128 HF

Used Sabroe SAB 128 HF screw compressor unit on NH<sub>3</sub>. Complete with a PLS225MR-T electric motor - 50 Hz - 75 kW - 2945 RPM, Sabroe OHU 4119 D oil separator with a volume of 270 liters, oil pump with a electric motor, Sabroe Unisab II control panel and a control box with Danfoss display. The compressor has a displacement of 454,0 m<sup>3</sup>/h at 2950 RPM and 546,0 m<sup>3</sup>/h at 3550 RPM.

\*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment solely if it has passed our extensive test. Warranty and industrial cleaning are included in your purchase. \*If requested we are happy to arrange your shipment.







