

Bitzer 4DC-7.2Y Condensing unit

Specifications

Brand	Bitzer
Туре	4DC-7.2Y Condensing
	unit
Refrigerant	Freon
kW at 0ºC/+40ºC	21,1
kW at -5ºC/+40ºC	17,5
kW at -10ºC/+40ºC	14,3
kW at -20ºC/+40ºC	9,3
kW at -30ºC/+40ºC	5,5
kW at -40ºC/+40ºC	2,8
On steel base frame	✓
Pressure safety switches	 Image: A start of the start of
Hp/Lp/Op	
Liquid receiver	 Image: A start of the start of
Liquid receiver ltr.	21
Oil separator	✓
Liquid line filter drier	✓
Sight Glass	 Image: A start of the start of
Solenoid Valve	✓
Control panel	 Image: A start of the start of
m3 / h	50 Hz - 28,0 m³/h / 60 Hz
	- 32,4 m³/h
Remarks	Y.o.b. 2001
Condensing Unit	 Image: A start of the start of
Sizes	1450x1120x1460 mm
	(LxWxH)
Stock	1



Description

Used Bitzer 4DC-7.2Y Condensing unit

Used condensing unit on Freon. Complete with a Bitzer 4DC-7.2Y semihermetic reciprocating compressor, condenser with 4 OLMO R11R-4035A-4M-5732 fans - 50 Hz -0,30 kW - 1390 RPM - diameter 400 mm, GVN VLR-21 liquid receiver with a volume of 21 liter, liquid receiver, oil separator, pressure and safety switches and a control cabinet. The compressor has a displacement of 28.0 m³/h at 50 Hz & 32,4 m³/h at 60 Hz. *Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment solely if it has passed our extensive test. Warranty and industrial cleaning are included in your purchase. *If requested we are happy to arrange



your shipment.



Your partner for used commercial and industrial refrigeration equipment











		Ritz	en	*			DC-7		
BITZE	ERK	HLMASC Made in		BAU G		S.Nr. 6	6604		
Nenr V A 3	span BPh~	nung V Y 3Ph~			tr.strom		strom A (Y)	Fördervol m ³ /h	Drehzah min ⁻¹
220-	-240	380-420	50	27,5	15,9	128,2	-74	28,04	1450
265	-290	440-480	60	27,5	15,9	128,2	74	32,4	1750
IP 6	5 N	D/HD max	K. 19 /	28 bar					"



Your partner for used commercial and industrial refrigeration equipment











Your partner for used commercial and industrial refrigeration equipment



