

Bitzer 4DES-5Y-40S (x1), 6HE-35Y-40P (x2) & 6FE-50Y-40P (x1) Condensing unit

Specifications

Brand	Bitzer
Type	4DES-5Y-40S (x1), 6HE-35Y-40P (x2) & 6FE-50Y-40P (x1) Condensing unit
Refrigerant	Freon
kW at 0°C/+40°C	326,9
kW at -5°C/+40°C	271,6
kW at -10°C/+40°C	223,6
kW at -20°C/+40°C	145,9
kW at -30°C/+40°C	89,1
On steel base frame	✓
Pressure safety switches	✓
Hp/Lp/Op	
Pressure gauges	✓
Hp/Lp/Op	
Liquid receiver	✓
Liquid receiver ltr.	400 l
Oil separator	✓
Oil level system AC&R	✓
Liquid line filter drier	✓
Sight Glass	✓
Solenoid Valve	✓
m ³ / h	399,5 m ³ /h - 50 Hz & 482,1 m ³ /h - 60 Hz



Remarks	Y.o.b. 2016
Condensing Unit	✓
Sizes	7500x2270x2400 mm (LxWxH)
Stock	1

Description

Used Bitzer 4DES-5Y-40S (x1), 6HE-35Y-40P (x2) & 6FE-50Y-40P (x1) Condensing unit

Used Bitzer condensing unit on Freon. Complete with a Bitzer 4DES-5Y-40S (x1), 6HE-35Y-40P (x2) & 6FE-50Y-40P (x1) semi-hermetic reciprocating compressors, Alfa Laval BCDS1003BD P condenser with 6 Ziehl-Abegg FN100-SDS.7Q.V5P1 fans - 50/60 Hz - 2,7/1,6-3,5/1,8-4,2/2,2 kW - 820/620-860/590-930/660 RPM, GVN N283-1005 liquid receiver H12A.400.B14.B14.F4.H4.F4 with a volume of 400 liters, AC&R S-1904-CE oil separator, AC&R S-9108-CE oil reservoir and pressure and safety switches/gauges. The compressors have a displacement of 50 Hz at 399,5 m³/h and 60 Hz at 482,1 m³/h.

*Why choose for HOSBV? We're not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment solely if it has passed our extensive test. Warranty and industrial cleaning are included in your purchase. *If requested we are happy to arrange your shipment.









