

Mycom FM160L-L

Specifications

Brand	Mycom
Type	FM160L-L
Refrigerant	NH 3 (ammonia)
kW at +10°C/+40°C	835,4
kW at 0°C/+40°C	579,6
kW at -5°C/+40°C	475,6
kW at -10°C/+40°C	385,6
kW at -20°C/+40°C	242,7
kW at -30°C/+40°C	140,7
kW at -40°C/+40°C	70,3
Unloaded Start	✓
Capacity Control	✓
On steel base frame	✓
Pressure gauges	✓
Hp/Lp/Op	
Oil separator	✓
Liquid line filter drier	✓
Sight Glass	✓
Control panel	✓
Condensing Unit	✓
Sizes	3150x1400x2300 mm (LxWxH)
Stock	1



Description

Used Mycom FM160L-L

Used Mycom FM160L-L screw compressor unit on NH3 (ammonia). Complete with Leroy Somer PLS280MC-T - 50/60 Hz - 132/152 kW - 2945/3548 RPM, Mycom HS6023-18/36-CE oil separator with a volume of 700 liters, KS12-AEP-123 L700 oil cooler, Mycom OFC50-18/36 oil filter, pressure gauges, Mycom F50P oil pump with electro motor - 50/60 Hz - 4,0/4,8 kW - 1415/1725 RPM and a control cabinet with a Mycom MYPRO-CP3 display. The compressor has a displacement of 949 m³/h.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

*Optional we can also perform a new



paint job and arrange the logistics.









