

# Bitzer 6FE-50Y-40P (x6) & 6F-50.2Y-40P (x1)

## Specifications

Brand	Bitzer
Type	6FE-50Y-40P (x6) & 6F-50.2Y-40P (x1)
Refrigerant	Freon
kW at 0°C/+40°C	869,3
kW at -5°C/+40°C	724,1
kW at -10°C/+40°C	597,4
kW at -20°C/+40°C	392,2
kW at -30°C/+40°C	241,0
kW at -40°C/+40°C	131,4
Capacity Control	✓
On steel base frame	✓
Pressure safety switches	✓
Hp/Lp/Op	
Pressure gauges	✓
Hp/Lp/Op	
Oil separator	✓
Oil level system AC&R	✓
Liquid line filter drier	✓
Sight Glass	✓
Solenoid Valve	✓
m <sup>3</sup> / h	1061 m <sup>3</sup> /h - 50 Hz & 1281,6 m <sup>3</sup> /h - 60 Hz
Weight in kg.	1650 kg
Package / Rack	✓



Sizes	3800x2700x2000 mm (LxWxH)
-------	------------------------------

Stock	1
-------	---

## Description

### **Used Bitzer 6FE-50Y-40P (x6) & 6F-50.2Y-40P (x1)**

Used semi-hermetic reciprocating Bitzer 6FE-50Y-40P (x6) & 6F-50.2Y-40P (x1) compressors rack on Freon. Complete with a 2 Henry Technologies S-5414-CE oil separators with volume of 40 liters, 2 Henry Technologies S-9108-CE oil reservoir, S-9530 oil level system AC&R, pressure and safety switches/gauges, control kast and frequency regulators: Omron SX-D4055-EV, Vacon0100-3L-0140 and x2 Omron CIMR-E7Z4011. The compressors have a total displacement of 1061 m<sup>3</sup>/h at 50 Hz and 1281,6 m<sup>3</sup>/h at 60 Hz.

\*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and an industrial cleaning.

\*Optionally we can also perform a new paint job and arrange the logistics.













