

Bitzer 4GE-30.2Y-40P (x1) & 4G-30.2 (x1) / 44G-60.2

Specifications

Brand	Bitzer
Туре	4GE-30.2Y-40P (x1) &
	4G-30.2 (x1) / 44G-60.2
Refrigerant	Freon
kW at 0°C/+40°C	137,1
kW at -5°C/+40°C	114,0
kW at -10ºC/+40ºC	93,9
kW at -20ºC/+40ºC	61,4
kW at -30ºC/+40ºC	37,2
kW at -40°C/+40°C	19,7
Pressure safety switches	; /
Hp/Lp/Op	
Oil level system AC&R	✓
Solenoid Valve	✓
m3 / h	169 m³/h
Weight in kg.	484 kg
Package / Rack	✓
Sizes	1550x700x650 mm
	(LxWxH)
Stock	1



Description

Used Bitzer 4GE-30.2Y-40P (x1) & 4G-30.2 (x1) / 44G-60.2

Used Bitzer 4GE-30Y-40P (x1) & 4G-30.2 (x1) / 44G-60.2 tandem semi-hermetic reciprocating compressor on Freon. Complete with a pressure and safety switch and an AC&R oil level system. The compressor has a displacement of 169 m³/h. *Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. *Optional we can also perform a new paint job and arrange the logistics.



Your partner for used commercial and industrial refrigeration equipment













info@hosbv.com



Your partner for used commercial and industrial refrigeration equipment



