

# Bitzer 6G-40.2Y-40P (x1) & 4VCS-10.2Y-40P (x1)

## Specifications

Brand	Bitzer
Type	6G-40.2Y-40P (x1) & 4VCS-10.2Y-40P (x1)
Refrigerant	Freon
kW at 0°C/+40°C	102,6/27,6*
kW at -5°C/+40°C	85,4/22,8*
kW at -10°C/+40°C	70,3/18,7*
kW at -20°C/+40°C	46,0/11,9*
kW at -30°C/+40°C	28,0/7,0*
kW at -40°C/+40°C	14,9/3,4*
On steel base frame	✓
Pressure safety switches	✓
Hp/Lp/Op	
Pressure gauges	✓
Hp/Lp/Op	
Condensing pressure switches	✓
Liquid receiver	✓
Liquid receiver ltr.	112
Oil separator	✓
Oil level system AC&R	✓
Liquid line filter drier	✓
Sight Glass	✓
Control panel	✓



	126,8 m <sup>3</sup> /h at 50 Hz & 153,1 m <sup>3</sup> /h at 60 Hz (4VCS-10.2Y-40P) 34,7 m <sup>3</sup> /h at 50 Hz & 41,9 m <sup>3</sup> /h at 60 Hz
Remarks	(6G-40.2Y-40P) (x1) & 4VCS-10.2Y-40P (x1) 2006 / (4VCS-10.2Y-40P) Y.o.b. 2005
Package / Rack	✓
Sizes	2050x1000x1950 mm (LxWxH)
Stock	1

## Description

### Used Bitzer 6G-40.2Y-40P (x1) & 4VCS-10.2Y-40P (x1)

Used Bitzer 6G-40.2Y (x1) & 4VCS-10.2Y-40P (x1) semi-hermetic reciprocating compressor rack on Freon. Complete with a Bitzer FS1122 liquid receiver with a volume of 112 liter, oil separator, oil reservoir, oil level regulators, liquid line filter drier, pressure and safety/switches and a control cabinet. The two compressors worked on their own cold room. The Bitzer 6G-40.2Y-40P has a displacement of 126,8 m<sup>3</sup>/h at 50 Hz & 153,1 m<sup>3</sup>/h at 60 Hz and the Bitzer 4VCS-10.2Y-40P has a displacement of 34,7 m<sup>3</sup>/h at 50 Hz & 41,9 m<sup>3</sup>/h at 60 Hz.

\*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

\*Optional we can also perform a new paint job and arrange the logistics.

















