

## Bitzer 4T-12.2 Y (x2) & 4V-10.2 Y (x2)

### Specifications

|                          |                                                              |
|--------------------------|--------------------------------------------------------------|
| Brand                    | Bitzer                                                       |
| Type                     | 4T-12.2 Y (x2) & 4V-10.2 Y (x2)                              |
| Refrigerant              | Freon                                                        |
| kW at 0°C/+40°C          | 119,0                                                        |
| kW at -5°C/+40°C         | 98,6                                                         |
| kW at -10°C/+40°C        | 81,0                                                         |
| kW at -20°C/+40°C        | 52,8                                                         |
| kW at -30°C/+40°C        | 32,0                                                         |
| kW at -40°C/+40°C        | 17,0                                                         |
| On steel base frame      | ✓                                                            |
| Pressure safety switches | ✓                                                            |
| Hp/Lp/Op                 |                                                              |
| Oil separator            | ✓                                                            |
| Oil level system AC&R    | ✓                                                            |
| Liquid line filter drier | ✓                                                            |
| Sight Glass              | ✓                                                            |
| m3 / h                   | 50 Hz - 144,86 m³/h / 60 Hz - 174,8 m³/h                     |
| Remarks                  | Y.o.b. 2003 (s.nr 1664905588)<br>y.o.b. 2001 (s.nr 66017473) |
| Package / Rack           | ✓                                                            |
| Sizes                    | 2400x850x1730 mm (LxWxH)                                     |
| Stock                    | 1                                                            |



### Description

#### Used Bitzer 4T-12.2 Y (x2) & 4V-10.2 Y (x2)

Used Bitzer 4T-12.2 Y (x2) & 4V-10.2 Y (x2) semi-hermetic reciprocating compressors rack on Freon. Complete with a Henry Technologie S-1902-CE with a volume of 8,1 liters, Henry Technologies S-9108U-CE oil reservoir, pressure and safety switches, oil level system and a liquid line filter drier. The compressors have a total displacement of 144,86 m³/h at 50 Hz and 174,8 m³/h at 60 Hz.

\*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

\*Optional we can also perform a new paint job and arrange the logistics.





