

## Bitzer 4N-20.2 Y (x3)

### Specifications

Brand	Bitzer
Type	4N-20.2 Y (x3)
Refrigerant	Freon
kW at 0°C/+40°C	137,4
kW at -5°C/+40°C	114,3
kW at -10°C/+40°C	93,9
kW at -20°C/+40°C	61,2
kW at -30°C/+40°C	37,2
kW at -40°C/+40°C	19,2
On steel base frame	✓
Pressure safety switches	✓
Hp/Lp/Op	
Pressure gauges	✓
Hp/Lp/Op	
Liquid receiver	✓
Liquid receiver ltr.	7,4
Oil separator	✓
Oil level system AC&R	✓
Liquid line filter drier	✓
Sight Glass	✓
m <sup>3</sup> / h	50 Hz - 168,3 m <sup>3</sup> /h & 60 Hz - 203,1 m <sup>3</sup> /h
Package / Rack	✓
Sizes	2115x1500x1200 mm (LxWxH)
Stock	1



### Description

#### Used Bitzer 4N-20.2 Y (x3)

Used Bitzer 4N-20.2 Y (x3) semi-hermetic reciprocating compressors on Freon. Complete with a Carly HCYR 81 oil receiver, Temprite 926 L oil separator, pressure and safety switches/gauges, oils levels systems AC&R and a filters drier. The compressors have a total displacement of 168,3 m<sup>3</sup>/h at 50 Hz & 203,1 m<sup>3</sup>/h at 60 Hz.

\*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we solely deliver our orders after performing an extensive test and an industrial cleaning. If requested we are happy to arrange your logistics.









