

## Bitzer 4H.2

### Specifications

|                          |                                                                                   |
|--------------------------|-----------------------------------------------------------------------------------|
| Brand                    | Bitzer                                                                            |
| Type                     | 4H.2                                                                              |
| Refrigerant              | Freon                                                                             |
| kW at 0°C/+40°C          | 54,8                                                                              |
| kW at -5°C/+40°C         | 45,7                                                                              |
| kW at -10°C/+40°C        | 37,7                                                                              |
| kW at -20°C/+40°C        | 24,8                                                                              |
| kW at -30°C/+40°C        | 15,3                                                                              |
| kW at -40°C/+40°C        | 8,4                                                                               |
| Electromotor Specs       | 15 kW at 1460 RPM                                                                 |
| Unloaded Start           | ✓                                                                                 |
| On steel base frame      | ✓                                                                                 |
| Pressure safety switches | ✓                                                                                 |
| Hp/Lp/Op                 |                                                                                   |
| Pressure gauges          | ✓                                                                                 |
| Hp/Lp/Op                 |                                                                                   |
| Liquid receiver          | ✓                                                                                 |
| Liquid line filter drier | ✓                                                                                 |
| Sight Glass              | ✓                                                                                 |
| Control panel            | ✓                                                                                 |
| Remarks                  | # // Electromotor: 15 kW at 1460 RPM // Pulley EM: 200 mm / Pulley compr.: 220 mm |
| Remarks                  | R404a - R22 or other freon types                                                  |



|      |                   |
|------|-------------------|
|      | (LxWxH)           |
| Size | 1650x1200x2200 mm |

## Description

### Used Bitzer 4H.2

Used Bitzer 4H.2 freon compressor, complete with unloaded start, pressure safety switches, pressure gauges, liquid receiver, liquid line filter drier, sight glass and control panel. This unit has a cooling capacity of 54,8 kW at 0°C/+40°C.

Why choose for HOSBV? We're not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and deliver after an industrial cleaning. \*If requested we are happy to arrange your logistics.





