

Bitzer 4G.2

Specifications

Brand	Bitzer
Туре	4G.2
Refrigerant	Freon
kW at 0°C/+40°C	74,5
kW at -5ºC/+40ºC	61,8
kW at -10°C/+40°C	50,6
kW at -20°C/+40°C	32,8
kW at -30°C/+40°C	19,7
kW at -40°C/+40°C	10,6
Electromotor Specs	18,5
Unloaded Start	/
On steel base frame	✓
Pressure safety switches	✓
Hp/Lp/Op	
Oil separator	/
Remarks	Electromotor: 18,5 kW at
	1460 RPM // Pully EM:
	230 mm / Pully compr.:
	220 mm
Remarks	R404a - R22 or other
	freon types
Sizes	1050x700x1000 mm
	(LxWxH)
Stock	1



Description

Used Bitzer 4G.2

Used Bitzer 4G.2 freon compressor, complete with unloaded start, pressure safety switches and oil separator. This unit has a cooling capacity of 74,5 kW at $0^{\circ}\text{C}/+40^{\circ}\text{C}$.

Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and deliver after an industrial cleaning. *If requested we are happy to arrange your logistics.



Your partner for used commercial and industrial refrigeration equipment







info@hosbv.com



Your partner for used commercial and industrial refrigeration equipment

