

Performer SZ110S4VA

Specifications

Brand	Performer
Туре	SZ110S4VA
Refrigerant	Freon
Refrigerant type	R407 C or other types
kW at +10°C/+40°C	32,7
kW at 0°C/+40°C	22,2
kW at -5°C/+40°C	18
Remarks	y.o.b. 2001
Sizes	300x350x580 mm
	(LxWxH)
Stock	1



Description

Used Performer SZ110S4VA

Used Performer SZ110S4VA freon scroll compressor. This unit has a cooling capacity of 32,7 kW at +10°C/+40°C.

Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and deliver after an industrial cleaning. *If requested we are happy to



Your partner for used commercial and industrial refrigeration equipment

arrange your logistics.

HOS BV www.hosbv.com info@hosbv.com (+31) (0)23-5404237



Your partner for used commercial and industrial refrigeration equipment







info@hosbv.com



Your partner for used commercial and industrial refrigeration equipment




COMPRESSOR MODEL DESIGNATION

Performer* scroll compressors are available both as single compressors and as tandem units. The example below presents single compressor nomenclature.

For tandem assemblies, please refer to the Performer* Parallel Application Guidelines documentation.

Nomenclature



Connection details

Model Version	SM/SZ 084 - 090 - 100 110 - 120 - 148 - 161 V	SM/SZ 115 - 125 - 160 - 175 - 185		SY/SZ 240 - 300		SY/SZ 380
		R	С	MA MB	AA AB	AA AB
Suction and discharge connection	brazed	rotolock	brazed	rotolock	brazed	brazed
Oil sight glass	threaded	threaded	threaded	threaded	threaded	threaded
Oil equalization connection	3/8" flare	3/8" flare	3/8" flare	1/2"flare	1/2" flare	1/2" flare
Oil drain connection	-	1/4"NPT	1/4" NPT	1/4"NPT	1/4" NPT	1/4" NPT
Low pressure gauge port (schrader)	1/4"flare	1/4"flare	1/4" flare	1/4"flare	1/4" flare	1/4" flare

HOS BV www.hosbv.com info@hosbv.com

(+31) (0)23-5404237