

Mycom 250 VSD

Specifications

| | |
|--------------------------|----------------------------------|
| Brand | Mycom |
| Type | 250 VSD |
| Refrigerant | Freon |
| kW at +10°C/+40°C | 1945 |
| kW at 0°C/+40°C | 1390,5 |
| kW at -5°C/+40°C | 1163,8 |
| kW at -10°C/+40°C | 966,6 |
| kW at -20°C/+40°C | 648,8 |
| kW at -30°C/+40°C | 416,2 |
| kW at -40°C/+40°C | 250,6 |
| Electromotor Specs | 315 kW at 2965 RPM |
| On steel base frame | ✓ |
| Pressure safety switches | ✓ |
| Hp/Lp/Op | |
| Pressure gauges | ✓ |
| Hp/Lp/Op | |
| Oil separator | ✓ |
| Control panel | ✓ |
| Remarks | R404a - R22 or other freon types |
| Package / Rack | ✓ |
| Stock | 1 |



Description

Used Mycom 250 VSD

Used Mycom 250 VSD freon compressor package, complete with pressure safety switches, pressure gauges, oil separator and control panel. This unit has a cooling capacity of 1945 kW at +10°C/+40°C.

Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and deliver after an industrial cleaning. *If requested we are happy to arrange your logistics.









