

Bitzer 6H.2

Specifications

| | |
|--------------------------|---|
| Brand | Bitzer |
| Type | 6H.2 |
| Refrigerant | Freon |
| kW at +10°C/+40°C | 116,8* |
| kW at 0°C/+40°C | 90 |
| kW at -5°C/+40°C | 74,9 |
| kW at -10°C/+40°C | 61,8 |
| kW at -20°C/+40°C | 40,7 |
| kW at -30°C/+40°C | 25,1 |
| kW at -40°C/+40°C | 13,8 |
| Electromotor Specs | 22 |
| Unloaded Start | ✓ |
| Capacity Control | ✓ |
| On steel base frame | ✓ |
| Pressure safety switches | ✓ |
| Hp/Lp/Op | |
| Remarks | # // Electromotor: 22 kW at 1460 RPM // *Capacity based on +7.5°C/+40°C |
| Remarks | R404a - R22 or other freon types |
| Package / Rack | ✓ |
| Sizes | 1600x450x700 mm (LxWxH) |
| Stock | 1 |



Description

Used Bitzer 6H.2

Used Bitzer 6H.2 freon compressor rack, complete with unloaded start, capacity control and pressure safety switches. This unit has a cooling capacity of 116,8 kW at +7.5°C/+40°C.

Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and deliver after an industrial cleaning. *If requested we are happy to arrange your logistics.

