

# Mycom 200VLD 3.6

## Specifications

|                          |                                       |
|--------------------------|---------------------------------------|
| Brand                    | Mycom                                 |
| Type                     | 200VLD 3.6                            |
| Refrigerant              | NH 3 (ammonia)                        |
| kW at +10°C/+40°C        | 1637,2                                |
| kW at 0°C/+40°C          | 1148,2                                |
| kW at -5°C/+40°C         | 949,4                                 |
| kW at -10°C/+40°C        | 777,5                                 |
| kW at -20°C/+40°C        | 504,5                                 |
| kW at -30°C/+40°C        | 309,9                                 |
| kW at -40°C/+40°C        | 176                                   |
| Electromotor Specs       | 250                                   |
| Unloaded Start           | ✓                                     |
| Capacity Control         | ✓                                     |
| On steel base frame      | ✓                                     |
| Pressure safety switches | ✓                                     |
| Hp/Lp/Op                 |                                       |
| Pressure gauges          | ✓                                     |
| Hp/Lp/Op                 |                                       |
| Oil separator            | ✓                                     |
| Sight Glass              | ✓                                     |
| Control panel            | ✓                                     |
| Remarks                  | # // Electromotor: 250 kW at 2970 RPM |
| Package / Rack           | ✓                                     |
| Sizes                    | 3200x1350x2500 mm (LxWxH)             |
| Stock                    | 1                                     |



## Description

### Used Mycom 200VLD 3.6

Used Compressor Unit Mycom 200VLD 3.6. This compressor unit has the following components: Electromotor Leroy Somer (250 kW at 2970 RPM), Oil Separator Mycom HS 7530 200, Oil Pump Mycom and Mycom control







