

Carrier 30 RA 080

Specifications

Brand	Carrier
Type	30 RA 080
Product type	Air Cooled Chiller
Capacity kW	79.0
Capacity Tons	22,4
Refrigerant	Freon
Refrigerant Type	R 407 C
Pump	✓
Weight in kg.	631
Sizes	2080x1080x1330 mm (LxWxH)
Remarks	Year of Manf: 14.10.2002
Stock	1



Description

Used Carrier 30 RA 080

Compressors: 2 pieces SZ185S4CC
Refrigerant: R 407 C Type: Air-Cooled
Chiller Internal pump: Yes Tons: 22,4
Fans: 1 piece Size: 2080x1080x1330 mm (LxWxH) Weight: 631kg **All components of this used chiller will be tested on good working, leak free condition (condensing blocks), compressors, fan, control panel, etcetera. Choosing HOSBV means buying with warranty. We perform an industrial cleaning and rust spots will be covered. Also, we can arrange your shipment.



Carrier						
3~ CF29/T						
N°900085 1999						
IP 55	cl.F	70 °C amb	Cp :	μF/V		
IK	kg	S1	c/h Cd :	μF/V		
V	Hz	min-1	kW	cos φ	A	°C
400	50	945	1,8	0,85	5,8	5,8
400	50	465	0,25	0,85	1,8	1,8



1 - NUMERO DE SÉRIE SERIAL NUMBER	12X242360
2 - MODELE - MODEL	30RA-080-A0140-PEE--
3 - VARIANTE - VARIANT	30RA
4 - ANNÉE DE FABRICATION ET DATE D'ESSAI YEAR OF MANUFACTURING AND TEST DATE	2002/10/14
5 - FLUIDE - MEDIUM R	407C
6 - GROUPE - GROUP	2
7 - CHARGES CIRCUIT A	18,0 kg
8 - CHARGES CIRCUIT B	0,0 kg
9 - FLUIDE DE CONFINEMENT CONFINEMENT MEDIUM	23 - --AZOTE--NITROGENE--
10 - PRESSION ADMISSIBLE MIN/MAX ALLOWABLE PRESSURE MIN/MAX (PS)	0,9 32,0 bar
11 - TEMPERATURES ADMISSIBLE MIN/MAX ALLOWABLE TEMPERATURE MIN/MAX (TS)	-20 7,2 °C
12 - PRESSION DE DÉCLANCHEMENT DES PRESSOSTATS PRESSURE SWITCH SETTING	29,0 bar
13 - PRESSION DE DÉCLANCHEMENT DES SOUPAPES SAFETY RELIEF VALVE SETTING	0,0 bar
14 - PRESSION D'ESSAI D'ÉTANCHÉITÉ DE L'UNITÉ UNIT LEAK TEST PRESSURE	15,0 bar
15 - TENSION VOLTAGE	400 v







