

Bitzer OSKA5361-K

Specifications


Brand	Bitzer
Type	OSKA5361-K
Refrigerant	NH 3 (ammonia)
kW at +10°C/+40°C	153.2
kW at 0°C/+40°C	106.0
kW at -5°C/+40°C	86.8
kW at -10°C/+40°C	70.2
Remarks	as good as new
Stock	1



Description

Used Bitzer OSKA5361-K

Used, well maintained Bitzer OSKA5361-K screw Ammonia NH3 refrigeration . Our capacity table is based on the used type of Freon. You can also use these compressors on alternative types of Freon. For all the other specs (if available), see the picture of the manufacturer model plate or the attached pdf file. *Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. *Optional we can also perform a new paint job and arrange the logistics.



bezogen auf 5 K Sauggasüberhitzung,
ohne Flüssigkeitsunterkühlung,
Motor-Drehzahl 2900 min⁻¹ (50 Hz)

based on 5 K suction superheat,
without liquid subcooling, motor speed
2900 min⁻¹ (50 Hz)

se référant à surchauffe à l'aspiration de 5 K,
sans sous-refroidissement de liquide,
vitesse du moteur 2900 min⁻¹ (50 Hz)




Klima-/Normalbereich		High-/Medium temperature range										Climatisation/Moyennes températures									
Verdichter Typ	Verf. Temp.	Kälteleistung Cooling capacity Puissance frigorifique										Leistungsaufnahme (Welle) Power consumption (shaft) Puissance absorbée (arbre)									
Compressor type	Cond. temp.	Verdampfungstemperatur °C										Pe [kW]									
Type de compresseur	Temp. de cond. °C	Saturated suction temperature °C										Température d'évaporation °C									
		12,5	10	7,5	5	0	-5	-10	-15	-20		12,5	10	7,5	5	0	-5	-10	-15	-20	
OSKA341-K	30	13000	11800	10600	9700	8700	8000	7400	6800	6400	6000	19,18	18,54	17,69	17,31	16,14	15,03	13,98	12,96	12,05	
	40	11800	10800	10200	9400	8500	7800	7200	6600	6200	5800	20,00	22,20	21,40	20,70	19,34	18,06	16,84	15,96		
	50	10600	10000	9400	8600	7700	7000	6400	5800	5400	5000	20,80	26,00	25,20	24,40	22,80	21,40	19,97	18,60		
OSKA351-K	30	15000	13800	12600	11700	10700	9900	9300	8700	8300	7900	22,80	22,10	21,30	20,60	19,21	17,90	16,65	15,47	14,35	
	40	14000	13000	11900	11000	10000	9200	8600	8000	7600	7200	23,70	26,40	25,60	24,70	23,00	21,60	20,00	18,60		
	50	13000	12000	10900	10000	9000	8200	7600	7000	6600	6200	31,90	31,00	30,20	29,10	27,20	25,50	23,80			
OSKA361-K	30	17000	16000	14800	13900	13000	12200	11600	11000	10600	10200	26,00	26,00	25,10	24,20	22,70	21,10	19,60	18,25	16,80	
	40	16000	15000	13800	12900	12000	11200	10600	10000	9600	9200	30,00	30,00	29,10	28,20	26,70	25,00	23,50			
	50	15000	14000	12900	12000	11100	10300	9700	9100	8700	8300	37,70	38,00	37,10	36,20	34,70	33,00	31,50			

Tiefkühlbereich
Economiser-Betrieb

Low temperature range
Economiser operation

Congélation
Fonctionnement avec économiseur







Your partner for used commercial and
industrial refrigeration equipment
