

# Bitzer 4G.2 cool/freeze aggregate installation

## Specifications

|                     |   |
|---------------------|---|
| Brand               | Bitzer                                  |
| Type                | 4G.2 cool/freeze aggregate installation |
| Refrigerant         | Freon                                   |
| Refrigerant type    | R 404 A or other types                  |
| kW at 0°C/+40°C     | 70.8                                    |
| kW at -5°C/+40°C    | 58.6                                    |
| kW at -10°C/+40°C   | 48.1                                    |
| kW at -20°C/+40°C   | 31.1                                    |
| kW at -30°C/+40°C   | 18.8                                    |
| Electromotor Specs  | 11                                      |
| Unloaded Start      | ✓                                       |
| Capacity Control    | ✓                                       |
| On steel base frame | ✓                                       |
| Stock               | 1                                       |



## Description

### Used Bitzer 4G.2 cool/freeze aggregate installation

Used Bitzer 4G.2 (Semi-hermetic Reciprocating piston Compressor aggregate. Our capacity table is based on the used type of Freon. You can also use these compressors on alternative types of Freon. For all the other specs (if available), see the picture of the manufacturer model plate or the attached pdf file. \*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. \*Optional we can also arrange the logistics.

