

Kuba SPB 35-G43

Specifications

Brand	Kuba
Type	SPB 35-G43
kW	9
Refrigerant	Glycol
Number of Fans	3
Fin Space in mm	7
Defrosting	Electric
m ³ /h	8.460
Sizes	2530x607x505mm (LxWxH)
Remarks	11.9kW is based on Freon and DT1 8K
Volume	11,3 dm ³
Stock	1



Description

Used Kuba SPB 35-G43

Used Kuba/Kelvion SPB 35-G43 evaporator with electric defrosting in the coil and diptray. 2 fans 50 Hz - 0,54 kW. Capacity based on glycol temperature in/out: -4/-2°C. Build in 2016.

*All components of this used evaporator will be tested on good working, leak free condition (electro engines), coils, bearings) Choosing HOSBV means buying with warranty. We perform a industrial cleaning. Also, we can arrange your shipment.





SPB ..F..

Type	Q ₀ = kW Q ₀ = kW		S	V _l	Dimensions (mm)			EURO		Option / Optie	
	IL1 ±0°C	IL1 -18°C			H	B	T	Standard	E. defrost	Goldlack	
	DT1 = 8K	DT1 = 7K	m ²	m ³ /h	Height	Width	Depth	SPB..F.	SPBE..F.	V6.01	V6.04
SPB 23-F21	0.9	0.6	2.8	980	351	760	400	720.00	828.00	252.00	108.00
SPB 23-F31	1.2	0.8	4.2	890	351	760	400	810.00	924.00	283.50	121.50
SPB 30-F21	1.5	1.1	4.3	1660	427	960	425	918.00	1101.00	321.00	138.00
SPB 30-F31	2.0	1.4	6.4	1590	427	960	425	1020.00	1224.00	357.00	153.00
SPB 30-F33	6.0	4.3	19.2	4770	427	2140	425	2160.00	2376.00	756.00	324.00
SPB 35-F23	7.2	5.3	19.8	9120	505	2530	607	2502.00	2752.50	876.00	375.00
SPB 35-F33	9.8	7.2	29.3	8620	505	2530	607	2752.50	3028.50	963.00	412.50
SPB 35-F43	11.9	8.8	38.7	8460	505	2530	607	3270.00	3597.00	1144.50	490.50
SPB 45-F33	16.9	12.1	50.2	15030	657	3130	613	4417.50	4726.50	1546.50	663.00
SPB 45-F43	20.6	14.9	66.4	14610	657	3130	613	4642.50	5061.00	1624.50	696.00
SPB 45-F53	19.1	26.4	82.7	16950	662	3130	573	6148.50	6732.00	2152.50	922.50

GEA Küba

NEW SP- LINE

SPB ..G..

Type	S	V _l	Dimensions (mm)			EURO		Option / Optie	
			H	B	T	Standard	E. defrost	Goldlack	
	m ²	m ³ /h	Height	Width	Depth	SPB ..G.	SPBE ..G.	V6.01	V6.04
SPB 23-G21	2.8	980	351	760	400	777.00	894.00	271.50	117.00
SPB 23-G31	4.2	890	351	760	400	874.50	997.50	306.00	130.50
SPB 30-G21	4.3	1660	427	960	425	991.50	1189.50	346.50	148.50
SPB 30-G31	6.4	1590	427	960	425	1101.00	1321.50	385.50	165.00
SPB 35-G21	6.6	3040	505	1130	607	1215.00	1350.00	426.00	183.00
SPB 35-G31	9.8	2940	505	1130	607	1456.50	1632.00	510.00	219.00
SPB 30-G23	13.0	4980	427	2140	425	2218.50	2437.50	777.00	333.00
SPB 30-G33	19.2	4770	427	2140	425	2332.50	2566.50	816.00	349.50
SPB 35-G23	19.8	9120	505	2530	607	2701.50	2973.00	945.00	405.00
SPB 35-G33	29.3	8820	505	2530	607	2973.00	3271.50	1041.00	445.50
SPB 35-G43	38.7	8460	505	2530	607	3531.00	3885.00	1236.00	529.50

