

Goedhart BSE 456-7-230 E

Specifications

Brand	Goedhart				
Туре	BSE 456-7-230 E				
kW	50.54				
Refrigerant	Freon				
Number of Fans	6				
Fin Space in mm	7				
Defrosting	Electric				
m³/h	27060				
Sizes	4985x500x690mm				
	(LxWxH)				
Volume	53 dm3				
Weight	284				
Stock	2				



Description

Used Goedhart BSE 456-7-230 E

Used well maintained Goedhart BSE 456-7-230 E evaporator with electric defrosting and 6 Fans, 27.060 m3/h, 4985x500x690mm (LxWxH), 53 dm3 **Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. Optional we can arrange shipment and export documents.



Your partner for used commercial and industrial refrigeration equipment



Boedhart Bohemia		Ťel.: # 420 (0)325 5 Fax: # 420 (0)325 5	1 99 52
Typ #	1	BSE 456-7-230	E
Sklad. / objedn. č. Stock nr.	1	600 335	
Ref. / výr. č. Ref. nr.		99-1398-030	-
Napětí - ventilátory Voltage - fans	:	400/50	VIHz
Příkon - ventilátory Power input - fans		1200	w
Napětí - eL odtávání Voltage - el. defrost	:	240/50	V/Hz
Příkon - el. odtávání Power input - el. defrost	:	22680	W
Zkušební tlak Test. pressure	:	25	bai
Max. pracovní tlak Max. work. pressure	:	19,5	ba
Vnitřní objem Internal volume	:	53	dr
Hmotnost netto Mass (empty)	:	284	
Vyrobe	no v The	České republice Czech Republic	

TYPE		CAPACITEIT (R22)						VENTILATOREN		CAPACITEIT (R22) EUROVENT/CECOMAF	
	Verdan	Verdampingstemp. = -5°C Gemiddelde luchttemp. = -18°C									
			DTM=6 -5/+1	DTM=8 -26/-18	DTM=7 -25/-18		Lucht- hoeveelheid	Туре		To=-8°C Lucht in=0°C	To=-25°C Luchtin=-18°C
	[W]	[W]	[W]	[W]	[W]	[W]	[m¾h]		[m²]	[W]	[W]
BSE 251-7	1120	870	615	960	730	570	870	1 x ø250	4	800	600
BSE 31A-7 BSE 31B-7	1830 2620	1430 2240	940 1820	1680 2060	1400 1860	1080 1580	1310 1230	1 x ø300 1 x ø300	6 10	1240 1820	1040 1440
BSE 32A-7	3680	2880	2390	3380	2810	2180	2630	2 x ø300	13	2660	2100
BSE 351-7 BSE 32B-7	4490 5250	3670 4490	2780 3660	3860 4810	3320 3990	2690 3160	2260 2460	1 x ø350 2 x ø300	15 19	2960 3660	2430 2880
BSE 401-7	6050	4950	4110	5390	4550	3610	3070	1 x ø400	20	4250	3270
BSE 451-7 BSE 352-7	8340 9000	6990 7380	5660 6050	7410 7740	6260 6650	4970 5400	4510 4520	1 x ø450 2 x ø350		5960 6260	4670 4880
BSE 402-7	12140	9920	8240	10800	9120	7240	6140	2 x ø400		8510	6550
BSE 452-7 BSE 453-7	16420 25090	14010 20600	11350 16970	14840 22270	12560 18870	9980 14970	9020 13530	2 x ø450 3 x ø450		11950 17860	9360 13650
BSE 454-7 BSE 455-7	33590 42660	28290 35570	22690 28050	29690 34250	25120 30140	19950 24170	18040	4 x ø450 5 x ø450	107 134	23900 29700	18700 23530
BSE 455-7 BSE 456-7	50540	35570	28050	34250	30140	29960	22550	5 X Ø450 6 X Ø450	161	35900	23530