

# Sabroe CMO 26

## Specifications

Brand	Sabroe
Type	CMO 26
Refrigerant	Freon
kW at +10°C/+40°C	155,7
kW at 0°C/+40°C	106,1
kW at -5°C/+40°C	86
kW at -10°C/+40°C	68,6
kW at -20°C/+40°C	41,3
kW at -30°C/+40°C	22,1
kW at -40°C/+40°C	9,3
Electromotor Specs	30kW at 1440RPM
On steel base frame	✓
Pressure safety switches	✓
Hp/Lp/Op	
Pressure gauges	✓
Hp/Lp/Op	
Remarks	Y.O.B 2006
Sizes	1450x650x920 mm (LxWxH)
Stock	1



## Description

### Used Sabroe CMO 26

Used Sabroe CMO 26 single-stage reciprocating compressor with electro motor build by Schorch with 30kW and 1440RPM at 50 \*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. \*Optional we can also arrange the logistics.







Model	Number of cylinders	Swept volume at 1500 rpm	Swept volume at 1800 rpm	Nominal capacities in kW at 1500 rpm						Dimensions in mm			Weight excluding motor	Sound pressure level at 1500 rpm (dB)
				B732						B40A				
				Single-high stage	Booster	Single-high stage				L	W	H		
		m³	m³	204-170°C	-40-0-20°C	0-17-30°C	20-30-10°C							
CMO 24	4	97	126	53	85	14	85	54	1400-2150	800	900	480	69	
CMO 26	6	146	175	79	127	21	127	61	1400-2175	800	900	520	71	
CMO 28	8	194	233	105	170	28	169	108	1475-2200	800	900	550	72	
CMO 34	4	113	136	62	100	17	99	63	1400-2150	800	900	480	70	
CMO 36	6	170	204	93	149	25	149	95	1480-2175	800	900	500	72	
CMO 38	8	228	273	123	209	33	198	127	1475-2200	800	900	550	73	

Nominal capacities are based on 1500 rpm and 5K liquid subcooling.  
 All refrigerants make it possible to operate CMO compressors  
 at speeds of up to 1800 rpm.  
 1500 rpm at 50 Hz.  
 1800 rpm at 60 Hz or VSD.

AKL0611 01.2019



Your partner for used commercial and  
industrial refrigeration equipment

---