

Bitzer 2GL-2.2 Tank aggregate

Specifications

Brand	Bitzer
Туре	2GL-2.2 Tank aggregate
Refrigerant	Freon
kW at +10ºC/+40ºC	5,53
kW at 0ºC/+40ºC	3,68
kW at -5ºC/+40ºC	2,95
kW at -10ºC/+40ºC	2,33
kW at -20ºC/+40ºC	1,37
kW at -30ºC/+40ºC	0,708
Unloaded Start	✓
On steel base frame	 Image: A start of the start of
Pressure safety switches	1
Hp/Lp/Op	
Condensing pressure	✓
switches	
Liquid receiver	✓
Liquid receiver ltr.	25
Liquid line filter drier	✓
Sight Glass	✓
m3 / h	7,56
Sizes	980x670x830 mm
	(LxWxH)
Stock	2



Description

Used Bitzer 2GL-2.2 Tank aggregate

Used Bitzer tank aggregate. Bitzer 2GL-2.2Y semi-hermetic reciprocating compressor with liquid receiver (25 liter).The tank Aggregate is equipped with pressure safety switches as well as pressure gauges. This tank aggregate has an unloaded start as well as a liquid line filter drier to optimize performance.

*Why choosing for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment and perform an extensive test and industrial cleaning. We are fully secure in the quality of our products and therefore every purchase comes with a warranty *on demand we are applying a new paint job and arrange all needed means of logistics.



Your partner for used commercial and industrial refrigeration equipment















