

Sabroe SAB 128 HF MK2 man VI

Specifications

Marca	Sabroe
Tipo	SAB 128 HF MK2 man VI
Refrigerante	NH 3 (ammonia)
kW at +10°C/+40°C	610,3
kW at 0°C/+40°C	423,2
kW at -5°C/+40°C	347,9
kW at -10°C/+40°C	283,2
kW at -20°C/+40°C	214,8
kW at -30°C/+40°C	134,7
kW at -40°C/+40°C	77,8
Electromotor Specs	50 Hz - 49,5 kW - 2950 RPM
Control de capacidad	✓
Sober Bancada	✓
Separador de aceite	✓
Mirilla	✓
Panel de control	✓
m3 / h	455,0
Tamaños	2350x1100x1530 mm (LxWxH)
Stock	1



Description

Used Sabroe SAB 128 HF MK2 man VI

Used Sabroe SAB 128 HF MK2 compressor unit on NH3. Complete with 1 Sabroe SAB 128 HF MK2 screw compressor, Schorch KA7225M-AB014-151 - 50 Hz - 49,5 kW - 2950 RPM elektromotor, oil separator, Sabroe OWSG 1615 oil cooler, oil filter, pump and a UNISAB S-control panel. The compressor can run as single cooling purpose with another electromotor.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. *If requested we are happy to arrange your logistics.





