

## Bitzer 6H-25.2Y-40P

### Specifications

|                            |                                       |
|----------------------------|---------------------------------------|
| Marca                      | Bitzer                                |
| Tipo                       | 6H-25.2Y-40P                          |
| Refrigerante               | Freon                                 |
| kW at -5°C/+40°C           | 70,6                                  |
| kW at -10°C/+40°C          | 57,0                                  |
| kW at -20°C/+40°C          | 35,8                                  |
| kW at -30°C/+40°C          | 20,8                                  |
| kW at -40°C/+40°C          | 10,6                                  |
| Electromotor Specs         | 380-420 V - 50 Hz - 45 A<br>- 28,9 kW |
| Recipiente de líquido      | ✓                                     |
| Recipiente de líquido ltr. | 54                                    |
| Acumulador de succión      | ✓                                     |
| Separador de aceite        | ✓                                     |
| Mirilla                    | ✓                                     |
| m3 / h                     | 110,5                                 |
| Comentarios                | Y.o.b 2004                            |
| Tamaños                    | 1650x470x950 mm<br>(LxWxH)            |
| Stock                      | 1                                     |



### Description

#### Used Bitzer 6H-25.2Y-40P

Used Bitzer 6H-25.2Y-40P semi-hermetic reciprocating compressor on freon. Complete with a suction line accumulator, oil separator Henry S-5590-CE and a 54 l liquid receiver Bitzer F552T.

\*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. \*if requested we are happy to arrange your logistics.





