

Bitzer 4N-20.2

Specifications

| | |
|----------------------------|----------------------------|
| Marca | Bitzer |
| Tipo | 4N-20.2 |
| Refrigerante | Freon |
| kW at 0°C/+40°C | 45,8 |
| kW at -5°C/+40°C | 38,1 |
| kW at -10°C/+40°C | 31,3 |
| kW at -20°C/+40°C | 20,4 |
| kW at -30°C/+40°C | 12,4 |
| kW at -40°C/+40°C | 6,7 |
| Sober Bancada | ✓ |
| Presostatos | ✓ |
| Recipiente de líquido | ✓ |
| Recipiente de líquido ltr. | 30 |
| La línea de líquido filtro | ✓ |
| secador | |
| Mirilla | ✓ |
| m3 / h | 56,1 |
| Tamaños | 910x1000x860 mm (LxWxH) |
| Stock | 1 |



Description

Used Bitzer 4N-20.2

Used Bitzer 4N-20.2 semi-hermetic reciprocating compressor on Freon. Complete with a Bitzer F 300 H with a volume of 30 liter, liquid line filter drier and pressure and safety switches. The compressor has a displacement of 56,1 m³/h.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

*Optional we can also perform a new paint job and arrange the logistics.

