

Airedale KKCS11-K66/6

Specifications

Brand	Airedale	
Тіро	KKCS11-K66/6	
Product type	Air Cooled Chiller	
Capacidad kW	34,5*	
Capacity Tons	9,8	
Refrigerante	Freon	
Tipo de Refrigerante	R407C	
Pump	1	
Peso kg.	330	
Sizes	1300x650x1600 mm	
	(LxWxH)	
Compressor(s) type &	1x Performer	
model	SZ185S4RC	
Display	CAL 3200	
Number of fans	2	
Fan specifications	50 Hz - 0,59 kW - 850	
	RPM - diameter 600 mm	
Remarks	Y.o.b. 2003	
Remarks	*Capacity based on	
	glycol 12/7°C and a	
	ambient temperature of	
	35°C	
Stock	1	



Description

Used Airedale KKCS11-K66/6

Used Airedale KKCS11-K66/S air cooled waterchiller on R407C. Complete with 1 Performer SZ185S4RC scroll compressor, braced plate heat exchanger as evaporator, condensor with 2 Ziehl-Abegg fans - 50 Hz - 0,59 kW - 850 RPM - diameter 600 mm, EBARA CDXH/A 120/07 water pump, expansion vessel and a CAL 3200 display.

*All components of this used chiller will be tested on good working, leak free condition condensing blocks, compressors, fans, control panel, etcetera. Choosing HOSBV means buying with warranty. We perform a industrial cleaning and rust spots will be covered. Also, we can arrange your shipment.







No.	AIREDALE air conditioning for every environment	
1 88	Unit / Gerät / Unite	₽ +44 113 2391000
100	Sorial (Onite	444 113 2507219
1959	Serial / Serie / Serie	KKCS11-K66/S
182	M.O. N° / Herstellungsreihenfolge / ordre industriel	81687405-001 81687405
麗	Sales Order N° / Bestell-Nummer / Numero de Commo	inde 63127189
200		
500	Manufactured / Hergestellt / Fabriqué	07/07/2003
	Supply / Spannung / Alimentation	400 V 3 PH 50 HZ
		50 A
1688	Fuse / Hauptsicherung / Fusibles	
		20.0BAR/
	Test Pressure / Prüfdruck / Pression D'Essa	LA Charge
	Kältemittel und Fülling / Réfrigen	R407C 8.50KG
	Refrigerant & Charge / Kältemittel und Fülling / Réfrigér	
	rterimal) / Pre	ession de marche
	Max Operating Pressure / Betriebsdruck (Maximal) / Pre	(t
	Max Operating Pressurer	10 M
	Iviax - r	
1		
. 153	www.airedale.com	
. 533	www.alreut	









'erformei SCROLL COMPRESSOR ODEL SZ185S4RC UF11 6038720 00 V 3 ~ 50 Hz LR 175 A FL'us CE BRICANT:P.O.E. 160SZ ATTENTION REFRIGERANTR407C R134a R404A R507A Danfoss P



















