

Bitzer 4EC-6.2Y-40S (x4)

Specifications

Marca	Bitzer
Tipo	4EC-6.2Y-40S (x4)
Refrigerante	Freon
kW at 0°C/+40°C	71,1
kW at -5°C/+40°C	59,0
kW at -10°C/+40°C	48,5
kW at -20°C/+40°C	31,4
kW at -30°C/+40°C	18,8
kW at -40°C/+40°C	9,7
Control de capacidad	✓
Sober Bancada	✓
Presostatos	✓
Manómetros de Presion	✓
Manómetros del	✓
Condensador	
Separador de aceite	✓
Sistema de nivel de aceite	✓
Valvula Solenoide	✓
m3 / h	90,8 - 109,6
Comentarios	Y.o.b. 2010
Package / Rack	✓
Tamaños	2360x850x1040 mm (LxWxH)
Stock	1



Description

Used Bitzer 4EC-6.2Y-40S (x4)

Used Bitzer 4EC-6.2Y-40S (x3) semi-hermetic reciprocating compressors on Freon. Complete with a Oilstar TOA-28H oil separator with a volume of 7,1 dm³, Oilstar TOS-7 oil reservoir with a volume of 7 dm³ and pressure and safety switches/gauges. The compressors have a combined displacement between 90,8 m³/h and 109,6 m³/h.

*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. *If requested we are happy to arrange your logistics.



TERO Gesellschaft für Kältetechnik mbH
 Carl-Benz-Straße 1
 63674 Altenstadt
 Deutschland

CE 0036

Modell: TPS4-4EC-6.2Y

Serien-Nr: 10030695 Baujahr: 03/2010

Betriebsstrom: max. 52.8 A

Verdichtertyp: 4x4EC-6.2Y

Heizung je Verdichter: 120 Watt bei 230 Volt

Kältemittel: / max. Füllgewicht: /

max. zuläss. Druck- HD: 28 bar max. zuläss. Druck- ND: 19 bar

	KW	Volt	Hz	max Betriebsstrom	Ph	Daten je Lüfter	KW	Volt	Hz	max Betriebsstrom	Ph
Daten je	7.9	400	50	13.2	Ampere	3	-	-	-	-	-
Verdichter	-	-	-	-	Ampere	-	-	-	-	-	-





