

## Bitzer 6F-50.2 (x2) / 66F-100.2

### Specifications

|                                    |                             |
|------------------------------------|-----------------------------|
| Marca                              | Bitzer                      |
| Tipo                               | 6F-50.2 (x2) / 66F-100.2    |
| Refrigerante                       | Freon                       |
| kW at 0°C/+40°C                    | 121,7                       |
| kW at -5°C/+40°C                   | 101,3                       |
| kW at -10°C/+40°C                  | 83,6                        |
| kW at -20°C/+40°C                  | 55,0                        |
| kW at -30°C/+40°C                  | 33,9                        |
| kW at -40°C/+40°C                  | 18,6                        |
| Sober Bancada                      | ✓                           |
| Presostatos                        | ✓                           |
| Manómetros de Presion              | ✓                           |
| Separador de aceite                | ✓                           |
| Sistema de nivel de aceite         | ✓                           |
| La línea de líquido filtro secador | ✓                           |
| Valvula Solenoide                  | ✓                           |
| Tamaños                            | 2200x750x1420 mm<br>(LxWxH) |
| Stock                              | 1                           |



### Description

#### Used Bitzer 6F-50.2 (x2) / 66F-100.2

Used Bitzer 6F-50.2 (x2) compressor unit on Freon. Complete with a Bitzer 66F-100.2 semi-hermetic tandem compressor, AC&R S -5203 oil separator, and pressure and safety switches/gauges.

\*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment solely if it has passed our extensive test. Warranty and industrial cleaning are included in your purchase.

\*If requested we are happy to arrange your shipment.







