

Bitzer IIIY Condensing Unit

Specifications

Marca	Bitzer
Tipo	IIY Condensing Unit
Refrigerante	Freon
kW at +10°C/+40°C	3,5*
kW at 0°C/+40°C	2,3*
kW at -5°C/+40°C	1,3*
kW at -10°C/+40°C	0,6*
kW at -20°C/+40°C	0,4*
Recipiente de líquido	✓
Recipiente de líquido ltr.	5,6 l
La línea de líquido filtro	✓
secador	
Mirilla	✓
m3 / h	4,0-9,4 m ³ /h
Comentarios	Y.o.b. 2006
Comentarios	* Freon type R404A and motor pulley 130mm
Condensing Unit	✓
Tamaños	850x600x620 mm (LxWxH)
Stock	1



Description

Used Bitzer IIIY Condensing Unit

Used Bitzer L40/IIY condensing unit on Freon. Complete with a Bitzer IIIY semi-hermetic reciprocating compressor, condenser with 1 fan, Bitzer FS 53 liquid receiver with a volume of 5,6 liters, rotor nl UD 0701/1048670-034-9 electric motor - 50/60 Hz - 6,4/3,45 kW - 1410/1710 RPM, Danfoss DML 083 liquid line filter drier and a sight glasses. The compressor has a displacement between 4,0 m³/h and 9,4 m³/h.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we solely deliver our orders after performing an extensive test and an industrial cleaning. If requested we are happy to arrange your logistics.







