

Helpman HTC 100-122-V/ 420 PREP

Specifications

Marca	Helpman
Tipo	HTC 100-122-V/ 420 PREP
Tipo de producto	Drycooler
Capacidad kW	133,7*
Número de aficionados	2
RPM de los ventiladores	420/310
Refrigerante	Glycol
Flujo de aire in m³/h	38.000
ventiladores de diámetro 1000 mm Ø	
Superficie (m2)	304
Volumen del tubo	25 dm³
Tamaños	4150x1250x1450 mm (LxWxH)
Peso	502 kg
Comentarios	Y.o.b. 2002
Remarks	*Capacity is based on a medium inlet temperature of 60°C and an outlet temperature of 40°C
Stock	1



Description

Used Helpman HTC 100-122-V/ 420 PREP

Used Helpman HTC 100-122-V drycooler. Complete with 2 Ziehl-Abegg FE100-NDS.6N.V7 fans - 50 Hz - 0,87/0,49 kW - 430/310 RPM - diameter 1000 mm and a total airflow of 38.000 m³/h.

The current condenser will be converted into a drycooler and the appropriate flanges will be installed. The drycooler has a capacity of 133,7kW with a medium inlet temperature of 60°C and an outlet temperature of 40°C.

*All components of this used condenser will be tested on adequate functionality, leak free condition (electro engines), condensing block,



bearings. Choosing HOSBV means buying with warranty. We perform an industrial cleaning on demand, we can arrange your shipment.



		Apparatenfabriek Helpman B.V. Peizerweg 97, 9727 AJ Groningen (NL) Tel. ++31 50 5217555 / Fax ++31 50 5264873 info@helpman.com / www.helpman.com	
Type	HTC 100.122-V/420 PREP		
Serial number	511292/120964-15944/01		
Refrigerant	R404A		
Operating temp.	100	°C (min/max)	
Design/test pressure	22/28	bar	year 2002
Internal volume	25.0	dm³	
Weight (empty)	502	kg	0134 



