

Mycom 200VMD 3.6

Specifications

Marca	Mycom
Tipo	200VMD 3.6
Refrigerante	NH 3 (ammonia)
kW at +10°C/+40°C	1357,8
kW at 0°C/+40°C	951,9
kW at -5°C/+40°C	786,8
kW at -10°C/+40°C	644,1
kW at -20°C/+40°C	417,5
kW at -30°C/+40°C	256,0
kW at -40°C/+40°C	144,9
kW at -45°C/+40°C	104,2
Sober Bancada	✓
Presostatos	✓
Manómetros de Presion	✓
Separador de aceite	✓
La línea de líquido filtro	✓
secador	
Mirilla	✓
Valvula Solenoide	✓
Panel de control	✓
Comentarios	*Liquid Subcooling 5°C. Suction Superheat 0°C. Rotation speed: 2950 RPM
Tamaños	3800x1600x2300 mm (LxWxH)
Stock	1



Description

Used Mycom 200VMD 3.6

Used Mycom 200VMD 3.6 screw compressor on NH3 (ammonia) type R717. Complete with a Leroy-Somer PLS315M-T electric motor - 50/60 Hz - 200/230 kW - 2960/3565 RPM, Mycom HS 7530-200 oil separator with a volume of 155 liters, Mycom OC-15245 oil cooler, x2 Mycom OFC 50 oil filter, Grundfos UPS 65-180/2F water pump, Mycom M80P oil pump with a Electramo 1AR132M2-6 electro motor - 50 Hz - 5,5 kW - 960 RPM, oil cooler and a control cabinet.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment soley if it has passed our extensive quality test and after it has been cleaned industrially. *If requested we are happy to arrange your



Your partner for used commercial and
industrial refrigeration equipment

shipment.









