

Bitzer 6G-40.2Y-40P

Specifications

Marca	Bitzer
Tipo	6G-40.2Y-40P
Refrigerante	Freon
kW at 0°C/+40°C	102,6
kW at -5°C/+40°C	85,4
kW at -10°C/+40°C	70,3
kW at -20°C/+40°C	46,0
kW at -30°C/+40°C	28,0
kW at -40°C/+40°C	14,9
Sober Bancada	✓
Presostatos	✓
Manómetros de Presion	✓
Recipiente de Líquido	✓
Recipiente de Líquido ltr.	160 l
Separador de aceite	✓
La línea de líquido filtro secador	✓
Mirilla	✓
m3 / h	50 Hz - 126,8 m ³ /h / 60 Hz - 152,9 m ³ /h
Comentarios	Y.o.b. 2003
Tamaños	1400x870x2420 mm (LxWxH)
Stock	1



Description

Used Bitzer 6G-40.2Y-40P

Used Bitzer 6G-40.2Y-40P semi-hermetic reciprocating compressor unit. Complete with a Bitzer FS1602 liquid receiver with volume of 160 liters, Henry Technologies S-5694-CE oil separator, pressure and safety switches/gauges, Danfoss liquid line filter drier and a sight glass. The displacement of the compressor is 126,8 m³/h at 50 Hz and 152,9 m³/h at 60 Hz.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and an industrial cleaning.

*Optionally we can also perform a new paint job and arrange the logistics.





