

Güntner GFH 102C/2*3 S (D)-F4 /3

Specifications

Marca	Güntner
Tipo	GFH 102C/2*3 S (D)-F4 /3
Tipo de producto	Drycooler
Capacidad kW	250,6
Número de aficionados	6
RPM de los ventiladores	430/310
Refrigerante	Glycol
Flujo de aire in m ³ /h	84.500
ventiladores de diámetro 1000 mm	∅
Superficie (m ²)	1190,5
Volumen del tubo	221 dm ³
Tamaños	7260x2400x1500 mm (LxWxH)
Stock	4



Description

Used Güntner GFH 102C/2*3 S (D)-F4 /3

Used Güntner GFH 102C/2*3S (D)-F4 /3 drycooler. Complete with 6 Ziehl-Abegg FE100-NDS.6N.V7 fans - 50 Hz - 0,50/0,19 kW - 430/310 RPM - diameter 1000 mm and a total airflow of 84.500 m³/h.

*Capacity based on the following:

Air inlet/outlet temperature:

25°C/33,9°C.

Medium Inlet/outlet temperature:

40°C/35°C.

Volume flow: 47,1 m³/h.

Medium: Glycol 34%.

Capacity of 625,1 kW based on the following:

Air inlet/outlet temperature:

25°C/47,3°C.

Medium Inlet/outlet temperature:
60°C/40°C.

Volume flow: 29,3 m³/h.

Medium: Glycol 34%.

*All components of this used condenser will be tested on adequate functionality, leak free condition (electro engines), condensing block, bearings. Choosing HOSBV means buying with warranty. We perform an industrial cleaning. on demand, we can arrange your shipment.





