

## Bitzer 4N-20.2 Y (x3)

### Specifications

Marca	Bitzer
Tipo	4N-20.2 Y (x3)
Refrigerante	Freon
kW at 0°C/+40°C	137,4
kW at -5°C/+40°C	114,3
kW at -10°C/+40°C	93,9
kW at -20°C/+40°C	61,2
kW at -30°C/+40°C	37,2
kW at -40°C/+40°C	19,2
Sober Bancada	✓
Presostatos	✓
Manómetros de Presion	✓
Recipiente de líquido	✓
Recipiente de líquido ltr.	7,4
Separador de aceite	✓
Sistema de nivel de aceite	✓
La línea de líquido filtro secador	✓
Mirilla	✓
m <sup>3</sup> / h	50 Hz - 168,3 m <sup>3</sup> /h & 60 Hz - 203,1 m <sup>3</sup> /h
Package / Rack	✓
Tamaños	2115x1500x1200 mm (LxWxH)
Stock	1



### Description

#### Used Bitzer 4N-20.2 Y (x3)

Used Bitzer 4N-20.2 Y (x3) semi-hermetic reciprocating compressors on Freon. Complete with a Carly HCYR 81 oil receiver, Temprite 926 L oil separator, pressure and safety switches/gauges, oil level system AC&R and a filter drier. The compressors have a total displacement of 168,3 m<sup>3</sup>/h at 50 Hz & 203,1 m<sup>3</sup>/h at 60 Hz. \*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we solely deliver our orders after performing an extensive test and an industrial cleaning. If requested we are happy to arrange your logistics.





