

Cabero GCHSD089MB/X7S-40 Y V

Specifications

| | |
|------------------------------------|-------------------------------|
| Marca | Cabero |
| Tipo | GCHSD089MB/X7S-40 Y V |
| Tipo de producto | Drycooler |
| Capacidad kW | 428,9 |
| Número de aficionados | 14 |
| RPM de los ventiladores | 770 |
| Refrigerante | Glycol |
| Flujo de aire in m ³ /h | 214.700 |
| ventiladores de diámetro 800 mm | Ø |
| Superficie (m2) | 3428,3 |
| Volumen del tubo | 560 |
| Tamaños | 12650x2360x1750 mm (LxWxH) |
| Comentarios | Y.o.b. 2020 |
| Stock | 2 |




Description

Used Cabero GCHSD089MB/X7S-40 Y V

Used Cabero GCHSD089MB/X7S-40 Y V dry cooler. Complete with 14 Ebm-papst W3G800-HG95-07 fans - 50/60 Hz - 0.9 kW - 770 rpm - diameter 800 mm, good for a total air flow of 214,700 m³/h. Furthermore, it comes with a control cabinet with a Ziehl-Abegg UNIcon fan controller.

*All components of this used chiller will be tested on good working, leak free condition condensing blocks, compressors, fans, control panel, etcetera. Choosing HOSBV means buying with warranty. We perform a industrial cleaning and rust spots will be covered. Also, we can arrange your shipment.



| | | | |
|---|---|--|--------------------------------|
| | | (2) PCN  | CABERO WÄRMETAUSCHER |
| (3) ITEM NO. GCHSD089MB/2X7S-40 Y V (EB) EC AXI A | | | |
| (4) SERIAL NO. 20-NL-5012-2 | (5) DESIGN CODE PED / DIN EN 14276:2 | (6) HEATING SURFACE 3428,3 M ² | |
| (7) FLUID ETHYLENE GLYCOL 30% / WATER 70% | | (8) FLUID GROUP 2 | |
| (9) MAX. ALLOWABLE PRESSURE (PS) 12 BAR | (10) APPLIED PRESSURE TEST (PT) 18 BAR | (11) PRESSURE TEST DATE 29.07.2020 | |
| (12) MIN. MAX. ALLOWABLE TEMP. (TS) -25 °C / +60 °C | (13) VOLUME 560 L | (14) FABRICATION YEAR 2020 | |
| (15) PED CATEGORY / MOD 0/- | (16) ADDITIONAL | | |
| <small>CABERO INDUSTRIAL KFT., KÜLTELEK 22, 7342 MÁGOC, HUNGARY T: +36 72 451-251, F: +36 72 451-020, INFO@CABERO.DE, WWW.CABERO.DE</small> | | | |

