

Rivacold RV4C0136 / 4HE-15Y-40P (x1) & 4PES-15Y-40P (x1) Condensing unit

Specifications

Marca	Rivacold
Tipo	RV4C0136 / 4HE-15Y-40P (x1) & 4PES-15Y-40P (x1) Condensing unit
Refrigerante	Freon
Refrigerant type	R134A
kW at 0°C/+40°C	62,4
kW at -5°C/+40°C	50,1
kW at -10°C/+40°C	39,6
kW at -20°C/+40°C	23,3
Sober Bancada	✓
Presostatos	✓
Manómetros de Presion	✓
Manómetros del	✓
Condensador	
Recipiente de líquido	✓
Acumulador de succión	✓
Sistema de nivel de aceite	✓
Mirilla	✓
Panel de control	✓
m3 / h	122 m ³ /h at 50 Hz & 162,1 m ³ /h at 60 Hz
Comentarios	Y.o.b. 2010



(LxWxH)

Medidas

3400x1450x1800 mm

Description

Used Rivacold RV4C0136 / 4HE-15Y-40P (x1) & 4PES-15Y-40P (x1) Condensing unit

Used Rivacold RV4C0136 air-cooled condensing unit on Freon. Complete with 1 Bitzer 4HE-15Y-40P (x1) & 4PES-15Y-40P (x1) semi-hermetic reciprocating compressors, condenser with 1 Ziehl-Abegg FN063-SDS.4I.V7P1 fan - 50 Hz - 0,62/0,44 kW - 900/720 RPM - diameter 630 mm & 2 Ziehl-Abegg FE063-ADA.4I.V7 fans - 50 Hz - 0,33/0,19 kW - 650/480 RPM - diameter 630 mm, 2 liquid receivers, 2 Danfoss VLT HVAC drives with each a Danfoss LCP 102 controller, control cabinet with a Danfoss EKAB 163B & 164B controller.

*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and an industrial cleaning. *Optionally we can also perform a new paint job and arrange the logistics.











