

Bitzer 4T-8.2Y (x2)

Specifications

Marca	Bitzer
Tipo	4T-8.2Y (x2)
Refrigerante	Freon
kW at -5°C/+40°C	54,3
kW at -10°C/+40°C	44,7
kW at -20°C/+40°C	29,1
kW at -30°C/+40°C	17,7
kW at -40°C/+40°C	9,5
Control de capacidad	✓
Sober Bancada	✓
Presostatos	✓
Manómetros de Presion	✓
Recipiente de Líquido	✓
Recipiente de Líquido ltr.	20 & 25
Acumulador de succión	✓
Mirilla	✓
Valvula Solenoide	✓
m3 / h	50 Hz - 78,8 m ³ /h & 60 Hz - 94,4 m ³ /h
Package / Rack	✓
Tamaños	1560x870x1560 mm (LxWxH)
Stock	1



Description

Used Bitzer 4T-8.2Y (x2)

Used Bitzer 4T-8.2Y (x2) semi-hermetic reciprocating compressor rack on Freon. Each compressor with it's own Bitzer FS liquid receiver, suction accumulator, liquid line filter drier and pressure and safety switches/gauges. The compressors have a total displacement of 78,8 m³/h at 50 Hz & 94,4 m³/h at 60 Hz. Please notice that the compressors are on their own circuit, but it's possible to make one. The capacity's are based on both compressors combined.

*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and an industrial cleaning. *Optionally we can also perform a new paint job and



arrange the logistics.





