

Bitzer 4T-12.2Y-40P

Specifications

Marca	Bitzer
Tipo	4T-12.2Y-40P
Refrigerante	Freon
kW at 0°C/+40°C	32,7
kW at -5°C/+40°C	27,1
kW at -10°C/+40°C	22,3
kW at -20°C/+40°C	14,6
kW at -30°C/+40°C	8,9
kW at -40°C/+40°C	4,8
kW at -45°C/+40°C	3,2
Piston Descargador	✓
Control de capacidad	✓
Mirilla	✓
Valvula Solenoide	✓
m3 / h	39,4 m ³ /h at 50 Hz & 47,5 m ³ /h at 60 Hz
Comentarios	Y.o.b. 2008
Peso kg.	146
Tamaños	700x540x490 mm (LxWxH)
Stock	1



Description

Used Bitzer 4T-12.2Y-40P

Used Bitzer 4T-12.2Y-40P semi-hermetic reciprocating compressor on Freon. Complete with unloaded start, capacity control and a sight glass. The compressor has a displacement of 39,4 m³/h at 50 Hz & 47,5 m³/h at 60 Hz.

*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and an industrial cleaning. *Optionally we can also perform a new paint job and arrange the logistics.

