

Bitzer HSN 7471-75-40P

Specifications

| | |
|---------------------------------------|------------------------------|
| Marca | Bitzer |
| Tipo | HSN 7471-75-40P |
| Refrigerante | Freon |
| Refrigerant type | R404A |
| kW at -20°C/+40°C | 120,3 |
| kW at -30°C/+40°C | 82,9 |
| kW at -40°C/+40°C | 54,5 |
| kW at -45°C/+40°C | 43,0 |
| Piston Descargador | ✓ |
| Control de capacidad | ✓ |
| Sober Bancada | ✓ |
| Presostatos | ✓ |
| Manómetros de Presion | ✓ |
| Recipiente de líquido | ✓ |
| Recipiente de líquido ltr. | 112 |
| Separador de aceite | ✓ |
| La línea de líquido filtro secador | ✓ |
| Mirilla | ✓ |
| Valvula Solenoide | ✓ |
| m3 / h | 250 |
| Comentarios | Y.o.b. 2011 |
| Tamaños | 1900x1050x2030 mm (LxWxH) |
| Stock | 1 |



Description

Used Bitzer HSN 7471-75-40P

Used Bitzer HSN7471-75-40P semi-hermetic screw compressor Freon on steel base frame. Complete with Bitzer F1202N liquid receiver, Bitzer OA1954 oil separator, Gea GBS 700M-20 brazed heat exchanger as economizer, Gea GBS 700M-44 brazed heat exchanger for heat recovery, pressure and safety switches/gauges and a liquid line filter drier. The compressor has a displacement of 250 m³/h at 2900 RPM and 300 m³/h at 3500 RPM. The capacities are with a economizer.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

*Optional we can also perform a new paint job and arrange the logistics.





